


AIR MULTI TRACK (NMTR L DOU ALI 48V)

Technical Information

Housing Material	Extruded Aluminum
Color	Electronic Powder Coating
Internal Lighting Track System	CV 48 magnetic track
Installation	Trimless Recessed
Custom Length Cutting	Available
Controllability	DALI on request
Plenum box (on request)	Extruded Aluminum



Dimensional Drawings



Ventilation Technical Information:

Noise Level (NC)	Static Pressure Loss ΔP_s (Pa)	3-Slot Throw $T_{0.75}$ (m)	3-Slot Airflow (CFM/LF)	2-Slot Throw $T_{0.75}$ (m)	2-Slot Airflow (CFM/LF)	1-Slot Throw $T_{0.75}$ (m)	1-Slot Airflow (CFM/LF)	Face Velocity (FPM)
21	7	2.2	126	2.8	84	3.1	42	450
22	10	2.4	141	3.1	94	3.3	47	500
23	12	2.6	155	3.4	103	3.5	52	550
24	15	2.8	169	3.8	113	3.9	56	600
25	18	3	183	4.1	122	4.2	61	650
26	21	3.2	197	4.4	131	4.4	66	700
26	24	3.4	211	4.8	141	4.6	70	750
27	28	3.6	225	5.2	150	4.8	75	800
28	35	3.9	253	5.8	169	5	85	900
29	43	4.2	281	6.5	188	5.1	94	1000
31	62	4.6	338	7.9	225	5.2	113	1200
32	86	5	394	9.2	263	5.2	131	1400
33	112	5.4	450	10.6	300	5.2	150	1600

Product Web Page



Product Catalog

